

MODEL 13138 ORBIS X/Y TRACKING ANTENNA

1.35 Meter Portable LEO / MEO / GEO



- *Tracks LEO, MEO, and GEO targets*
- *Integrated High Performance Servo Control System with Precision Tracking*
- *Full Motion X/Y Pedestal for overhead tracking.*
- *High Speed Retrace > 15 deg / sec*
- *Multi-Band capable with interchangeable feeds*
- *Integrated L Band Beacon Receiver with Optional Spectrum Analyzer*
- *Precision Carbon Fiber Reflector, No Special Tools / Bolt Together Design*
- *Portable / No Tools required for assembly.*



The Sat-Lite Technologies Model 13138 X/Y Antenna is a high performance full motion antenna designed to track satellites in LEO / MEO/ and GEO orbits. The portable packs in 3 cases plus an RF / Integration case and can be assembled in 20 minutes or less. The high performance servo system is configured to automatically determine an accurate heading and track satellites using TLE or an integral beacon receiver. Multiple tracking algorithms are available. The X/Y pedestal provides +/- 90 degrees of travel in both axes for full overhead pass with high speed retrace capability.

Multiple feed configurations can be provided including L, S, X, Ku, and Ka Bands. Amplifier integration and packaging options are available.



Electrical Specifications	2 Port X Band Circular		2 Port Cross Pol Ku Band Circular		4 Port Cross Pol Ka Band Circular	
	Rx	Tx	Rx	Tx	Rx	Tx
Frequency (GHz)	7.25 - 7.75	7.9 - 8.4	10.7 - 12.75	13.75 - 14.5	17.7 - 21.2	27.5 - 31.0
Gain (Midband, dBi)	38.2	38.8	42.5	43.8	46.4	49.8
Typ. Noise Temperature (K)						
10 deg EI	74		79		155	
20 deg EI	65		70		115	
Axial Ratio	1.21 dB	2.0 dB	1.5 dB	1.5 dB	1.5 dB	1.0 dB
Cross Pol (std)						
On Axis	-23 dB	-18.7 dB	-21.3 dB	-21.3 dB	-21.3 dB	-24.8 dB
in 1 dB BW	-23 dB	-18.7 dB	-21.3 dB	-21.3 dB	-21.3 dB	-24.8 dB
Sidlobe Compliances	188-164B		ITU 580-6		ITU 580-6	
VSWR	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Isolation						
Tx/Tx						17 dB
Rx/Rx					17 dB	
Tx/Rx	-110 dB	0 dB input	-85 dB	0 dB input	-85 dB	0 dB input
Rx/Tx	0 dB input	-110 dB	0 dB input	-35 dB	0 dB input	-70 dB
Max Power Handling (Continuous)		250 W		200 W		100 W

Mechanical / Environmental Specifications	
Reflector	1.35 M Carbon Fiber
Reflector Configuration	11 Piece Symmetrical
Antenna Travel	
X-Axis (lower axis)	+/-90° continuous, > 15 deg / sec
Y-Axis (upper axis)	0 - 180°, > 15 deg / sec
Polarization	Optional
Packaging (3 Cases)	
Reflector (SKB 3i-2922-16)	32 x 24.75 x 16.875 (60 lbs)
Positioner (Pelican iM3075)	33.3 x 24.4 x 19.3 (90 lbs)
Pedestal / Controller Components (SKB 3026-15)	33.75 x 28.5 x 16.25 (115 lbs)
RF Case - optional per band and BUC configuration	
Servo Control System	
Pedestal Mounted with Ethernet Interface	90 - 265 VAC Input Power, 500 Watts
Autolocate Features	GPS / Compass
Tracking	Multiple Options Sun Tracking / TLE Trackng
Temperature	
Operational	-20 to 60°C (-4 to 140°F)
Survival	-40 to 70°C (-40 - 158°F)
Winds	
Operational (anchored)	30 mph Gusting to 45 mph (48 kph G 72 kph)
Survival (anchored, petals removed)	75 mph
Integration	
Rear Mounted BUCs / LNBS	Packs in Integration Case
Rain	
Operational	4 in/h (10 cm/h)
Survival	6 in/h (15 cm/h)
Relative Humidity	0 - 100%
S Performance dependent on proper installation	360 btu/h/ft ² (1000 Kcal/h/m ²)
R Note: Specifications subject to change without notice	1 in (25.4 mm)
Corrosive Atmosphere	As encountered in coastal and/or industrial areas