

3841 PELORIS

3.8 Meter Motorized Vehicle-Mount Antenna



- *Intelsat / Eutelsat Compliant (with Appropriate Feed)*
- *Multi-Band C, X, Ku or Ka band Frequencies*
- *Multiple Integration Options*
- *Integrated Controller with Tracking Options Available*
- *Carbon Fiber Reinforced Reflector Polymer Structure*
- *Low Profile and Space-Optimizing Stow Position*
- *Cable Drive Positioning System*
- *Superior Stability in Wind*
- *Excellent Reliability*
- *Minimal Maintenance*
- *Segmented Reflector for Transportability*

The Sat-Lite Technologies Model 3841 vehicle-mount 3.8 M antenna is a high performance compact multi-band antenna designed for the most demanding environments. This antenna features a carbon fiber composite reflector and aluminum backbeam structure designed to provide exceptional performance along with a custom-designed elevation-over-azimuth cable drive pedestal to reduce vehicle mounting space.

The antenna is designed to meet international performance specifications for commercial or military applications and is available in C, X, Ku and Ka band frequencies. Multiple feed configurations and integration options are available. Also included is a high performance control system capable of precision tracking, auto stowing, jog control and auto locating of satellites using GPS/Compass or dual GPS options.



TECHNICAL SPECIFICATIONS



Standard Electrical Specifications	2 Port C Band Extended Linear Feed		4 Port C Band Std. Circular Feed		2 Port X Band Circular Polarization		2 Port Cross-Pol Ku Band Linear Mode Matched Feed		4 Port Ka Band Circular Polarization	
	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx
Frequency (GHz)	3.4 - 4.2	5.85 - 6.725	3.625 - 4.2	5.85 - 6.725	7.25-7.75	7.9-8.4	10.7 - 12.75	13.75 - 14.5	17.7 - 21.2	27.5 - 31
Gain (midband, dBi)	41.8	46.2	42.0	46.1	47.3	47.9	51.5	53.2	55.0	58.3
Noise Temperature (K) (Includes Insertion Loss)					(Includes Filter Losses)					
5 deg El	56		61		75		75		200	
10 deg El	51		55		62		62		168	
20 deg El	45		50		56		55		130	
40 deg El	42		46		53		50		103	
Cross Pol										
On Axis	-30 dB	-35 dB	-21.3 dB	-27.3 dB	-21.3 dB	-21.3 dB	-35 dB	-35 dB	-27.3 dB	-30 dB
in 1 dB BW	-28 dB	-28 dB	-21.3 dB	-27.3 dB	-21.3 dB	-21.3 dB	-25 dB	-35 dB	-27.3 dB	-30 dB
Axial Ratio			1.5 dB	0.75 dB	1.5 dB	1.5 dB			< 0.75 dB	< 0.5 dB
Sidelobe Compliances	Meets ITU 580-6 Or IESS (Intelsat)		Meets ITU 580-6 Or IESS (Intelsat)		Meets ITU 580-6 or Mil STD 188-164A		Meets ITU, FCC 25.209, Eutelsat		Meets ITU 580-6 or Mil STD 188-164A	
VSWR	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.40:1	1.30:1	1.35:1	1.30:1
Isolation										
Tx/Rx	-85 dB	0 dB input	-85 dB	0 dB input	-115 dB	0 dB input	-85 dB	0 dB input	-85 dB	0 dB input
Rx/Tx	0 dB input	-85 dB	0 dB input	-85 dB	0 dB input	-115 dB	0 dB input	-45 dB	0 dB input	-70 dB
Max Power Handling (Continuous)	1.0 kW		1.0 kW		1.0 kW		1.0 kW		200 W	
WG Interface	CPR-229	CPRG-137	CPR-229	CPRG-137	WR112	WR112	WR75-Cover	WR75-Cover	WR42	WR34

Mechanical/Environmental Specifications	
Reflector	3.8 meters (150 in) - Carbon Fiber
Antenna Travel	
Azimuth	300° continuous (+/- 150°)
Elevation	0 - 90° of reflector boresight
Polarization	± 95°
Antenna Drive Rate	
Azimuth (Brushless Servo Motor)	up to 1°/sec (Higher Speeds Optional)
Elevation (Brushless Servo Motor)	up to 0.5°/sec (Higher Speeds Optional)
Polarization (24 VDC Motor)	up to 2°/sec (Higher Speeds Optional)
Temperature	
Operational	-30 to 60°C (-22 - 140°F)
Survival	-40 to 70°C (-40 - 158°F)
Pointing Loss (operational winds)	2 dB Typical (Ku-band Rx)
Winds ¹	
Operational	30 mph Gusting to 45 mph (48 kph G 72 kph)
Operational with Servo Control	45 mph Gusting to 60 mph (72 kph G 96 kph)
Survival	70 mph (112 kph) any position
	125 mph (200 kph) stowed
Antenna Dimensions	
Stowed	Length: 194" (493 cm) Width: 90" (229 cm) Height: 48 in (122 cm)
Deployed	Width 150" (380 cm) Deployed
Weight	2900 lb (1318 kg) - without feed/integration
Integration	
Feedboom Mounted ²	225 lbs (102 kg)
Rain	
Operational	4 in/h (10 cm/h)
Survival	6 in/h (15 cm/h)
Relative Humidity	0 - 100%
Solar Radiation	360 btu/h/ft ² (1000 Kcal/h/m ²)
Corrosive Atmosphere	As encountered in coastal and/or industrial areas

* Using appropriate tracking controller ** Contact Factory
 1 Dependent on vehicle capabilities
 2 Dependent on mounting position relative to elevation axis
 Note: Specifications subject to change without notice