

2021 Agilis

2.0 Meter Carbon Fiber Flyaway Antenna



The Sat-Lite Technologies Model 2021 Agilis carbon fiber flyaway antenna offers superior performance in a lightweight, portable package. This antenna features a 7 piece carbon fiber segmented reflector designed to provide high gain and low cross pol characteristics. The custom-designed elevation-over-azimuth tripod pedestal provides high stiffness with minimal weight. The antenna components are modular in design which provides options for motorization and tracking requirements. High performance molded cases are included.

The antenna is designed to meet international performance specifications for commercial or off-the-shelf military applications and is readily available in C, X, Ku, DBS and Ka band frequencies. Multiple feed and integration packages are available with a quick change / quick pack configuration. The integrated boom assembly with BUC and LNB packs in a single case for quick installation. Integrated feedbooms can be supplied which will allow a quick change from one frequency band to another.

- **Intelsat & Eutelsat Compliant (Using Appropriate Feed)**
- **Multi-Band C, X, Ku, DBS and Ka Band Frequencies**
- **Integrated Feedboom Assembly Option**
- **Compact Packaging – Packs in 4 Cases**
- **Excellent Stability in Wind**
- **Minimal Maintenance and High Reliability**
- **Less than 15 min Assembly Time**
- **Captive Hardware – No Tools for Assembly**
- **Fully Motorized Configuration Available**



TECHNICAL SPECIFICATIONS



| 2.0 Meter RF Specifications | 2 Port Cross-Pol C Band Extended Linear Feed | | 2 Port Cross-Pol C Band Circular Feed | | 2 Port X Band Circular Polarization | | 2 Port Cross-Pol Ku Band Linear / Mode Matched Feed | | 2 Port Ka Band Circular Polarization | |
|-----------------------------|--|-------------|---------------------------------------|-------------|-------------------------------------|-------------|---|---------------|--------------------------------------|-------------|
| | Rx | Tx | Rx | Tx | Rx | Tx | Rx | Tx | Rx | Tx |
| | Frequency (GHz) | 3.40 - 4.20 | 5.85 - 6.725 | 3.625 - 4.2 | 5.85 - 6.425 | 7.25 - 7.75 | 7.9 - 8.4 | 10.95 - 12.75 | 13.75 - 14.5 | 20.2 - 21.2 |
| Gain (Midband, dBi) | 36.6 | 40.5 | 36.5 | 40.5 | 42.0 | 42.6 | 46.1 | 47.8 | 50.5 | 53.7 |
| Noise Temperature (K) | | | | | | | | | | |
| 10 deg EI | 52 | | 55 | | 68 | | 53 | | 144 | |
| 20 deg EI | 45 | | 49 | | 64 | | 48 | | 120 | |
| Cross Pol | | | | | | | | | | |
| On Axis | -30 dB | -30 dB | -20 dB | -27 dB | -30 dB | -30 dB | -35 dB | -35 dB | -21.3 dB | -24.8 dB |
| in 1 dB BW | -26 dB | -26 dB | -20 dB | -27 dB | -30 dB | -30 dB | -25 dB | -35 dB | -21.3 dB | -24.8 dB |
| Axial Ratio | | | 1.6 dB | 0.75 dB | 0.5 dB | 0.5 dB | | | 1.5 dB | 1 dB |
| Sidelobe Compliances | Meets ITU 580 Beyond Mainbeam | | Meets ITU 580 Beyond Mainbeam | | Mil-Std 188-164 | | ITU, FCC Eutelsat | | Mil-Std 188-164 | |
| VSWR | 1.40:1 | 1.30:1 | 1.35:1 | 1.30:1 | 1.30:1 | 1.30:1 | 1.35:1 | 1.30:1 | 1.35:1 | 1.30:1 |
| Isolation | | | | | | | | | | |
| Tx/Rx | -85 dB | 0 dB input | -85 dB | 0 dB input | -110 dB | 0 dB input | -85 dB | 0 dB input | -85 dB | 0 dB input |
| Rx/Tx | 0 dB input | -35 dB | 0 dB input | -50 dB | 0 dB input | -110 dB | 0 dB input | -30 dB | 0 dB input | -30 dB |

| Mechanical / Environmental Specifications | |
|--|--|
| Reflector | 2.0 meters (78.75 in) Carbon Fiber |
| Reflector Configuration | Parabolic Single Offset, 0.8 F/D (7 pieces) |
| Antenna Travel | |
| Azimuth | 360° continuous with fine adjust |
| Elevation | 5 - 90° of reflector bore sight |
| Polarization | ± 90° |
| Antenna Packaging | |
| Case 1 - Backbeam & Legs | 44.9" x 25.3" x 16.5" (99 lbs) |
| Case 2 - Az Hub, El Strut, Foot Pads | 37.5" x 27.5" x 14.5" (99 lbs) |
| Case 3 & 4 - (7 piece reflector) | 42" x 13" x 34.5" (75 lbs ea.) |
| Total Weight (less feed options) | 348 lbs (158 kg) |
| Temperature | |
| Operational | -30 to 60°C (-22 to 140°F) |
| Survival | -40 to 70°C (-48 to 158°F) |
| Pointing Loss (operational winds) | 3dB peak (Ku-band Rx) |
| Winds | |
| Operational (C Band Typical) | 30 Gusting to 45 mph (40 kph G 72 kph) with ballast or anchors |
| Optional Wind Strut Accessory | 45 mph (72 kph) |
| Survival | 60 mph (96 kph) with tie downs / any position |
| Feedboom Mounted Integration | 60 lbs (27.2 kg) |
| Rain | |
| Operational | 2 in/h (5 cm/h) |
| Survival | 4 in/h (10 cm/h) |
| Relative Humidity | 0 - 100% (condensing) |
| Solar Radiation | 360 btu/h/ft ² (1000 Kcal/h/m ²) |
| Radial Ice (survival) | 1/2 in (12.7 mm) |
| Corrosive Atmosphere | As encountered in coastal and/or industrial areas |

* Feed packaged separately dependent on options ordered
 ** Performance dependent on proper installation and ballast/anchors
 *** Dependent on position of weight. Consult Engineering for details
 Note: Specifications subject to change without notice.